


**PRODUCT**

# Hazard Marking Tape

## TECHNICAL DATASHEET

**DESCRIPTION**

Highly visible hazard marking tape for marking outside EPAs. The tape is made from a heavy duty plasticised film coated with an aggressive pressure sensitive adhesive for a strong hold.

**COLOURS**

**147-0011**  
Red/White



**147-0012**  
Black/Yellow



**147-0022**  
Black/White



**147-0023**  
Green/White


**FEATURES**

- Durable
- 50mm wide and 33m long
- 0.15mm thick

**APPLICATION**

- Factory demarcation and hazardous areas

PRODUCT CODE	DESCRIPTION	SIZE (METRIC)	SIZE (IMPERIAL)	COLOUR	QUANTITY
147-0011	Hazard Marking Tape	50mm x 33m	2in x 108.3ft	Red & White	Per Roll
147-0012	Hazard Marking Tape	50mm x 33m	2in x 108.3ft	Black & Yellow	Per Roll
147-0022	Hazard Marking Tape	50mm x 33m	2in x 108.3ft	Black & White	Per Roll
147-0023	Hazard Marking Tape	50mm x 33m	2in x 108.3ft	Green & White	Per Roll

To request a quotation or for more information, please call **+44 (0)1473 836200**  
 email [info@antistat.co.uk](mailto:info@antistat.co.uk) or visit [www.antistat.co.uk](http://www.antistat.co.uk)

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2025 Antistat.

## SPECIFICATIONS

TECHNICAL PROPERTIES	RESULT
Tape Thickness	0.15mm
Tensile strength at Break	28.0N / 10mm
Elongation at Break	150%
Adhesion to Steel	2.0N / 10mm
Adhesion to Self	2.0N / 10mm
Water Extract (1g tape per 100ml) PH	6.0 to 8.0
Conductivity	Max 2.5mS/m
Service Temperature	0°C to 6-°C
Application Temperature	5°C to 40°C
Recommended Storage Temperature	10°C
Shelf Life	12 months
Width of Tape	Cut to order
Appropriate Specification	BS3887: (1991) Part 2 Category 1 All colours DEF.STAN 75.7/1

To request a quotation or for more information, please call **+44 (0)1473 836200**  
 email [info@antistat.co.uk](mailto:info@antistat.co.uk) or visit [www.antistat.co.uk](http://www.antistat.co.uk)

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2025 Antistat.